

**Electra Glide/Ultra/Road Glide/Road King/Street Glide**  
**2009 - 2013**  
**ONE Piece Seat**  
**Ultimate Seats Installation**

**Install kit for Road King, Street Glide, Road Glide (for optional sissy bar pad)**

**3 stainless spacers**

**3 screws 1/4" – 20 x 1.5" long**

**Removal of Stock Seat**

1. If you have a seat strap remove saddlebags.
2. Remove the two saddlebag mount brackets (one each side) holding the seat strap.
3. Remove the strap and store it then replace the two saddlebag mounts in their original position.
4. Remove the rear fender bolt from seat.
5. Slide seat back and up to remove.



Fig 1



Fig 2



Fig 3

**Install your New Seat**

(If you have purchased a heated Ultimate Seat, please follow steps 1 to 3, if not, please skip to 4).

1. Find bike accessory plug located directly behind tank figure 1.
2. Plug supplied jumper into bike plug in figure 2.
3. Plug Ultimate Seat into jumper Figure 3.
4. Install your Ultimate seat now, make sure you have the front locating bracket on the seat nose located properly in the bike frame under the tank and install the stock screw in the rear bracket on the seat and fasten correctly.
5. Reinstall your saddlebags.

**Remove/Install sissy bar pad (optional)**

Remove the 3 screws holding the stock pad and remove, store the pad and the plastic spacers.

Install the Ultimate pad using the 3 supplied stainless spacers and install with the stock screws, if they are not long enough use the new supplied screws.

**Questions?**  
**877-672-0288**  
**des@ultimateseats.com**  
**www.ultimateseats.com**

4/6/2017