

**Electra Glide/Ultra/Road Glide**  
**Road King/Street glide**  
1997 – 2007  
**Ultimate seats Installation - 2 pc seat set**

**Install kit** - Two grooved chrome dome nuts

**Removal of Stock Seat**

1. Remove saddlebags.
2. Remove the two saddlebag mount brackets (one each side) holding the seat strap.
3. Remove the strap and store it then replace the two saddlebag mounts in their original position.
4. Remove the rear fender bolt from seat.
5. Slide seat back and up to remove.
6. Remove the Harley driver backrest mount.

**Install your new seats.**

1. Install the supplied chrome tank filler if you have a Electra Gide Ultra Glide or Ultra Classic.
2. Remove the two nuts from the rear fender bolts, leave the two white plastic washers in place.
3. Install your Ultimate front seat now, make sure you have the front locating bracket on the seat nose located properly in the bike frame under the tank and then line up the two exposed threads in the fender with the rear bracket on the seat.
4. Install the two supplied chrome dome nuts to secure the seat, lightly tighten with a wrench but do not over tighten.
5. Now install your Ultimate passenger seat by sliding the bracket on the front of the seat into the grooves in the chrome locking nuts.
6. Install the original bolt into the rear passenger seat bracket and fasten correctly.
7. Reinstall your saddlebags.

**Remove/Install sissybar pad (optional)**

Remove the 3 screws holding the stock pad and remove, store the pad.  
If the backing plate for your sissy bar is flat, reuse the spacers from your stock bar.  
If the backing plate for your sissy bar is the styled model no spacers required.  
Install the Ultimate pad using the 3 stock screws.

Enjoy the ride again on your Ultimate seats.

**Questions ?**  
**877-672-0288**  
**des@ultimateseats.ca**  
**www.ultimateseats.ca**

4/11/2025