

**INDIAN Chief Family**  
**All models and years except Roadmaster**  
**TWO PC SEAT (bolted together)**  
**Ultimate Seats Installation**

**Removal of Stock Seat set**

1. Remove the side covers both sides.
2. Remove the passenger backrest (sissy bar)
3. Remove the bolts on each side of the driver seat.
4. Remove the rear fender bolt from the passenger seat.
5. Slide seat set back and up to remove.

**Install your new seat set**

Note: If you have Captain Itch heat shield, it will need to be modified like Fig. 3.

Note: If you have purchased our heated seat set, please remove the bracket pictured in Fig. 2 if installed on your Chief. Then plug the Ultimate Seat into the OEM heat plug socket.

1. Install your Ultimate seat set now, make sure you have the front locating bracket on the seat nose located properly in the bike frame under the tank and reinstall the stock screws in the front seat and rear passenger bracket.
2. Reinstall your side covers.

**Note:** If you have the Indian® Concert Audio Kit (Part# 2879816) installed, the amp must be relocated from the factory suggested mounting location (Fig 1)



**Fig 1**



**Fig 2**



**Fig 3**

**Remove/Install sissy bar pad (optional)**

Reinstall your passenger backrest (sissy bar)

Remove the 2 screws holding the stock pad and remove, store the pad.

Install the Ultimate pad using the 2 stock bolts.

**Solo seat install**

The Ultimate Solo installs exactly like stock with the side bolts.

If you have the Indian luggage rack it bolts to our seat with two 3/8" - 24 button head bolts.

The bolts are supplied with our solo seat if ordered as a solo.

**Questions?**

**877-672-0288**

**des@ultimateseats.com**

**www.ultimateseats.com**