

Ultimate seats install

DYNA®

Wide Glide®/Super Glide/StreetBob®/FatBob®/SwitchBack®

2006 and up seat installation

Install kit

1 fender nut

1 pan head screw ¼" x ½" long

1 zip tie

1 spool and ¼" x 1" long button head screw (for passenger seat only)

Removal of Stock Seat

1. Remove the screw from the rear of the seat.
2. Lift up and back to remove the seat.

Install your new rider seat

1. Remove the plastic plug in the center of the rear fender.
2. Install the supplied fender nut.
3. Use the zip tie to hold the nut and feed the zip tie up through the hole in the fender from underneath, when in place insert the spring clip to secure the nut.
4. Now install your Ultimate rider seat by sliding the bracket on the front of the seat under the tank bracket and secure the rear bracket using the supplied pan head screw (if solo)

Install passenger seat

Remove the 4 square rubber pads from the fender and store away.

Use the supplied spool and button head screw ¼" x 1" in place of the pan head screw on top of the rear bracket to secure the rider seat. Install the passenger seat by sliding the fork front bracket into the spool groove and secure with the original rear screw in the fender.

Enjoy the ride again on your Ultimate seats.

Questions ?

877-672-0288

des@ultimateseats.ca

www.ultimateseats.ca