

INDIAN ROADMASTER
All models and years
TWO PC SEAT (bolted together)
Ultimate Seats Installation

Removal of Stock Seat set

1. Remove the side covers both sides.
2. Remove the bolts on each side of the driver seat.
3. Open the trunk and remove the 12V plug.
4. Remove the rear fender bolt from the passenger seat through the plug hole, see (Fig. 1)

Note: you can also remove the trunk from the bike.

5. Slide seat set back and up then forward to remove.
6. Unplug the seat electrical harness.



Fig. 1



Fig. 2



Fig. 3



Fig. 4

Note: If you have the Indian® Concert Audio Kit (Part# 2879816) installed, the amp must be relocated from the factory suggested mounting location.

Install your new Ultimate seat set

Note: If you have Captain Itch heat shield, it will need to be modified like Fig. 3 above.

Note: If you have purchased our heated seat set, please remove the bracket pictured in Fig. 4 if installed on your Roadmaster. Then plug the Ultimate Seat into the OEM heat plug socket.

1. Install your Ultimate seat now, make sure you have the front locating bracket on the seat nose located properly in the bike frame under the tank and reinstall the stock screws in the front seat and rear passenger bracket.
2. Reinstall your side covers.

Solo seat install

Note: must be ordered as a solo seat to have the solo rack attachment in the seat.

The Ultimate Solo installs exactly like stock with the side bolts.

If you have the Indian luggage rack it bolts to our seat with two 3/8"x16 button head bolts.

The bolts are supplied with our solo seat only when ordered as a solo.

Questions?
877-672-0288
des@ultimateseats.com
www.ultimateseats.com