

**Electra Glide/Ultra/Road Glide
Road King/Street glide
2008 to 2013
Ultimate seats Installation – 2 pc seat**

Install kit

2 grooved chrome dome nuts

3 stainless spacers and 3 screws ¼” – 20 x 1.5” long (for optional sissybar pad)

Removal of Stock Seat

1. Remove saddlebags.
2. Remove the two saddlebag mount brackets (one each side) holding the seat strap.
3. Remove the strap and store it then replace the two saddlebag mounts in their original position.
4. Remove the rear fender bolt from seat.
5. Slide seat back and up to remove.

Install your new seats.

1. Remove the two nuts from the rear fender bolts, leave the two white plastic washers in place.
2. Install your Ultimate front seat now, make sure you have the front locating bracket on the seat located properly in the bike frame and line up the two exposed threads in the fender with the rear bracket on the seat.
3. Install the two supplied chrome dome nuts to secure the seat, lightly tighten with a wrench but do not over tighten.
4. Now install your Ultimate passenger seat by sliding the bracket on the front of the seat into the grooves in the locking nuts.
5. Install the original bolt into the rear passenger seat bracket and fasten correctly.
6. Reinstall your saddlebags.

Remove/Install sissybar pad (optional)

Remove the 3 screws holding the stock pad and remove, store the pad and the plastic spacers.
Install the Ultimate pad using the 3 supplied stainless spacers and install with the stock screws, if they are not long enough use the new supplied screws.

Enjoy the ride again on your Ultimate seats.

**Questions ?
877-672-0288
des@ultimateseats.ca
www.ultimateseats.ca**