

# **Indian Chief Family 2014 and Up**

## **Two Piece Seat (Bolted Together)**

### **Ultimate Seats Installation**

#### **Removal of Stock Seat Set:**

1. Remove the quick release passenger backrest. (sissy bar)
2. Remove the side covers from both sides.
3. Remove the bolts on each side of the driver seat.
4. Remove the rear fender bolt from the passenger seat.
5. Slide seat set back and up to remove.

#### **Install Your New Seat Set:**

**Installation Note 1:** If you have a **Captain Itch Heat Shield**, it will need to be modified to fit with your Ultimate Seat. If you indicated with your order that you use a Captain Itch Heat Shield, a template to cut the shield was supplied with your new Ultimate Seat as well as 2 button head bolts (M8 x 35mm) that replace the OEM tank bolts indicated in Fig 1. After the heat shield is modified install it under the seat on the front locator bracket then install the seat with it attached Fig 2.

**Installation Note 2:** Remove the OEM driver backrest bracket if it is installed on your bike.

**Installation Note 3:** If you have purchased our heated seat set, remove the bracket pictured in Fig. 3.

**Installation Note 4:** If you have the Indian® Concert Audio Kit (Part #2879816) installed, the amp must be relocated from the factory suggested mounting location Fig 4.

**Installation Note 5:** If you have the Indian luggage rack that bolts to the passenger backrest (sissy bar), Replace the hex bolts with the 2 button head bolts provided (M8 x 25mm) if you indicated use of a luggage rack when you placed your order.



**Fig 1**



**Fig 2**



**Fig 3**



**Fig 4**

1. Bolt the Ultimate passenger seat to the driver seat using the supplied flat head bolt ¼”-20 x 1½” long.  
Note the supplied nylon washer installs between the passenger bracket and the driver seat base pan.
2. If you have purchased our heated seat set, then plug the Ultimate Seat into the OEM heat plug socket.
3. Install your Ultimate seat set now, make sure you have the front locating bracket on the seat nose located properly in the bike frame under the tank and reinstall the stock screws in the front seat and rear passenger bracket.
4. Reinstall your side covers.

#### **Remove/Install sissy bar pad (optional)**

Reinstall your passenger backrest (sissy bar)

Remove the 2 screws holding the stock pad and remove, store the pad.

Install the Ultimate pad using the 2 stock bolts.

#### **Solo Seat Install**

The Ultimate Solo installs exactly like stock with the side bolts.

If you have the Indian solo luggage rack it bolts to our seat with two 3/8” x 16 x 1” button head bolts.

**Questions?**

**877-672-0288**

**des@ultimateseats.com**

**www.ultimateseats.com**

**05/01/2018**