

The Ultimate passenger armrest **YAMAHA ARMREST INSTALLATION**

Installs on Yamaha round bar Tall only backrest sissy bar.

To check if you have the correct height sissybar measure from the top of the fender right behind the passenger seat to the top of the round chrome sissybar, should be between 14" and 17".

Before you start, place a thick cloth over the fender below the area you will be working for protection if you drop the parts.

- 1. Remove the hinge pin so the clamp bar and the armrest are separated.**
- 2. Take the clamp on bar and standing behind the Sissy Bar mount the U bolts onto the sissybar and through the clamp bar, finger tight nuts only at this time.**
- 3. Place the clamp on bar just under the backrest pad and remount the armrest with the hinge pin.**
- 4. Have your passenger sit on the bike and make the height adjustment (on Road Star tall bar only) all other bars the U bolt clamps are on the bend section of the bar.**
- 5. Tighten the U bolt nuts to secure the assembly (do not over tighten)**
- 6. When dismounting you must first flip up the armrest Do not use them to push yourself up They are not intended to be used in this manner. Please make sure your passenger is told this. Damage to the hinge will occur if they are used incorrectly.**

Your new armrest has a quick release hinge pin so if you wish to remove the armrest and leave the mounting bracket attached to the backrest sissybar just pull the retainer sleeve and slide out the hinge pin.



Questions or comments des@ultimateseats.ca

Toll free 1-877-672 0288

www.ultimateseats.ca