

Indian Challenger

Ultimate Seats Installation

Install kit

M8 X 25 mm long button head bolts = 2 (only need if you have a luggage rack)

Heated Seat Adapter = 1 (only supplied with Ultimate heated seats)

Removal of Stock Seat

1. Remove the sissy bar or trunk from the bike.
2. Remove the side covers both sides and remove the seat bolts.
3. Slide seat back and then lift up and off the bike.
4. If you have the Indian driver backrest you must **remove the receiving bracket** from the bike before installing our seat
4. **If you are installing a heated Ultimate Seat**, locate the 12v accessory plug that is wrapped up in electrical tape on your main harness (Fig 1). Install the supplied heated seat adapter.
5. **If you are installing an Ultimate Seat with an Indian Trunk, the Ultimate Sissy Bar and Trunk Relocation Kit must be installed prior to trunk reinstallation. Also, p-clamps are provided on the bottom of the seat to route the trunk harness through).**
6. All the mounting brackets are already installed on your new seat.
7. Install the two stock seat bolts and tighten.
8. Replace both side covers.

If You Have a Luggage Rack on Your Sissy Bar:

Replace the two hex head bolts in the sissybar holding the luggage rack with the **two button head bolts supplied**.

Note: because our passenger seat is longer you must install the seat first and then install the sissy bar or trunk. To increase passenger space when using a sissy bar - install our optional sissy bar and trunk relocation kit.



Questions ?

877-672-0288

des@ultimateseats.ca

www.ultimateseats.ca

Enjoy the ride again on your Ultimate seat.